



Model: SQC1540-6 (S)		
Standby Power (60Hz)	1540KVA/1232KW	
Prime Power(60Hz)	1400KVA/1120KW	

Standard Features

• Engine: Cummins KTA50-G3

Charge Alternator: 24V

Governer: Electronic

 Generator: Stamford HCI634K Single Bearing Alternator IP23

· Insulation Class H/H

· Genuine radiator with engine driven fan

Skid and vibration isolators

Dry type air filter

Main line circuit breaker (Below 500KVA)

12V battery and cable

User's manual



Weight And Dimensions			
Genset	Dimensions(LxWxH)	Weight (KG)	
Open type	5000mmx1850mmx2343mm	9150	
Silent type	12192mmx2438mmx2896mm	17020	

Generator Ratings					
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	60	3	0.8	1540/1232	1400/1120

Criterion

• Generator sets: GB/T2820-1997, ISO9001: 2008

Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359

Diesel Engine: ISO3046, DIN6271





SANQ Sanq Power

Engine Data	
Manufacturer/Model	CCEC Cummins KTA50-G3
 No.of Cylinders 	16
Displacement	50.3L
 Bore and Stroke 	159*159(mm)
Compression ratio	13.9:1
Rated RPM	1800rpm
 Max.standby power at rated 1800RPM 	1380KW
Aspiration	Turbocharged and aftercooled
Governor Type	GAC governor
 Exhaust Gas Flow @Standby Rating 	4541L/S
 Exhaust Temperature @Standby Rating 	531℃
 Intake Air Flow@Standby Rating 	1694liter/s
Fuel System	Direct Injection Cummins PT
• 100%(Prime Power) Load	282Liter/H
 Lubrication System Min. capacity 	121L
 Total Coolant Capacity 	161L

Alternator Data		
 Manufacture/Type 	Stamford/HCI634K	
 Number of phase power 	3	
• Factor	0.8	
Pole Number	4	
 Bearing Number 	1	
Exciter Type	Brushless, self-excited	
 Insulation Class 	H/H	
Protection	IP23	

Control Panel



- Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 7320 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.
- Features: receive remote output signal from ATS and realize auto start and stop of generators.
- Auto Mains Failure controller, can realize further more can detect ATS and control directly.
- •RS232 or 485 interface which can communicate with PC to realize remote operation.







• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

Optional

Engine	Alternator	Fuel System	Control System
Pre-heater	Anti Condensation HeaterDrop CT (For Paralleling)	•	Remote Control PanelAuto Transfer Switch (ATS)Paralleling System
			 Electricity Output Cabinet

Others

- · Rainproof Type
- Soundproof Type
- Trailer Type
- Container Type
- Spare Parts















Warranty





Data Sheet

SANO Sanq Power

- Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Cummins gensets enjoy world-wide united Warranty from Cummins engine agency or service centre at the client's local side.
- Service and parts are available from Guangzhou Sanq Power Equipment Co., Ltd or our distributors in your location.





