



Model: SQC390 (S)		
Standby Power (50Hz)	390KVA/312KW	
Prime Power(50Hz)	354KVA/283KW	

Standard Features

• Engine: Cummins NTA855-G4

Charge Alternator: 24V

Governer: Electronic

Generator: Stamford HCI444E

Single Bearing Alternator IP23

· Insulation Class H/H

· Genuine radiator with engine driven fan

Skid and vibration isolators

Dry type air filter

Main line circuit breaker (Below 500KVA)

12V battery and cable

User's manual



Weight And Dimensions			
Genset	Dimensions(LxWxH)	Weight (KG)	
Open type	3000mmx1054mmx1758mm	3280	
Silent type	4300mmx1483mmx2145mm	4495	

Generator Ratings					
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	50	3	0.8	390/312	354/283

Criterion

• Generator sets: GB/T2820-1997, ISO9001: 2008

Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359

Diesel Engine: ISO3046, DIN6271





SANO Sand Power

Engine Data	
Manufacturer/Model	CCEC Cummins NTA855-G4
No.of Cylinders	6
Displacement	14L
 Bore and Stroke 	140*152(mm)
 Compression ratio 	14.0:1
Rated RPM	1500rpm
 Max.standby power at rated 1500RPM 	351KW
Aspiration	Turbocharged,Aftercooled
Governor Type	Electronic
 Exhaust Gas Flow @Standby Rating 	1128L/S
 Exhaust Temperature @Standby Rating 	524℃
 Intake Air Flow@Standby Rating 	408liter/s
Fuel System	Direct Injection Cummins PT
 100%(Prime Power) Load 	75Liter/H
 Lubrication System Min. capacity 	36L
Total Coolant Capacity	20.8L

Alternator Data		
 Manufacture/Type 	Stamford/HCI444E	
 Number of phase power 	3	
• Factor	0.8	
Pole Number	4	
 Bearing Number 	1	
Exciter Type	Brushless, self-excited	
 Insulation Class 	H/H	
Protection	IP23	

Control Panel



- Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 7320 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.
- Features: receive remote output signal from ATS and realize auto start and stop of generators.
- Auto Mains Failure controller, can realize further more can detect ATS and control directly.
- •RS232 or 485 interface which can communicate with PC to realize remote operation.







• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

Optional

Engine	Alternator	Fuel System	Control System
Pre-heater	Anti Condensation HeaterDrop CT (For Paralleling)	•	Remote Control PanelAuto Transfer Switch (ATS)Paralleling System
			 Electricity Output Cabinet

Others

- · Rainproof Type
- Soundproof Type
- Trailer Type
- Container Type
- Spare Parts















Warranty





Data Sheet

SANO Sanq Power

- Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Cummins gensets enjoy world-wide united Warranty from Cummins engine agency or service centre at the client's local side.
- Service and parts are available from Guangzhou Sanq Power Equipment Co., Ltd or our distributors in your location.





