



Model: SQC550 (S)	
Standby Power (50Hz)	550KVA/440KW
Prime Power(50Hz)	500KVA/400KW

Standard Features

• Engine: Cummins QSZ13-G3

Charge Alternator: 24V

Governer: Electronic

 Generator: Stamford HCI544D Single Bearing Alternator IP23

· Insulation Class H/H

· Genuine radiator with engine driven fan

Skid and vibration isolators

Dry type air filter

Main line circuit breaker (Below 500KVA)

12V battery and cable

User's manual



Weight And Dimensions			
Genset	Dimensions(LxWxH)	Weight (KG)	
Open type	3250mmx1360mmx2100mm	3700	
Silent type	4600mmx1600mmx2300mm	6450	

Generator Ratings					
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	50	3	0.8	550/440	500/400

Criterion

• Generator sets: GB/T2820-1997, ISO9001: 2008

Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359

Diesel Engine: ISO3046, DIN6271







SANO Sanq Power

Engine Data	
Manufacturer/Model	DCEC Cummins QSZ13-G3
 No.of Cylinders 	6
Displacement	13L
Bore and Stroke	130*163(mm)
Compression ratio	17.0:1
Rated RPM	1500rpm
 Max.standby power at rated 1500RPM 	470KW
 Aspiration 	Turbocharged Charge Air Cooled
Governor Type	Electronic
 Exhaust Gas Flow @Standby Rating 	37.3kg/min
 Exhaust Temperature @Standby Rating 	547℃
 Intake Air Flow@Standby Rating 	30.3m3/min
Fuel System	Direct Injection Cummins PT
• 100%(Prime Power) Load	101Liter/H
 Lubrication System Min. 	45.42L
Total Coolant Capacity	23.1L

Alternator Data		
 Manufacture/Type 	Stamford/HCI544D	
 Number of phase power 	3	
• Factor	0.8	
Pole Number	4	
 Bearing Number 	1	
Exciter Type	Brushless, self-excited	
 Insulation Class 	H/H	
 Protection 	IP23	

Control Panel



- Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 6020 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.
- Features: receive remote output signal from ATS and realize auto start and stop of generators.
- Auto Mains Failure controller, can realize further more can detect ATS and control directly.







• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

Optional

Engine	Alternator	Fuel System	Control System
Pre-heater	Anti Condensation HeaterDrop CT (For Paralleling)	•	Remote Control PanelAuto Transfer Switch (ATS)Paralleling System
			 Electricity Output Cabinet

Others

- · Rainproof Type
- Soundproof Type
- Trailer Type
- Container Type
- Spare Parts















Warranty







SANO Sanq Power

- Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Cummins gensets enjoy world-wide united Warranty from Cummins engine agency or service centre at the client's local side.
- Service and parts are available from Guangzhou Sanq Power Equipment Co., Ltd or our distributors in your location.







