# QSAND Sanq Power

Standby Power (50Hz)	700KVA/560KW
Prime Power(50Hz)	630KVA/504KW

# **Standard Features**

- Engine: Cummins KT38-G
- Charge Alternator: 24V
- Governer: Electronic
- Generator: Stamford HCI544F
- Single Bearing Alternator IP23
- Insulation Class H/H
- Genuine radiator with engine driven fan
- Skid and vibration isolators
- Dry type air filter
- Main line circuit breaker (Below 500KVA)
- 12V battery and cable
- User's manual

# Weight And Dimensions

Genset	Dimensions(LxWxH)	Weight (KG)	
Open type	3525mmx1550mmx2032mm	4220	
Silent type	5000mmx1983mmx2371mm	6700	

Generator Ratings					
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	50	3	0.8	700/560	630/504

### Criterion

- Generator sets: GB/T2820-1997, ISO9001: 2008
- Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359
- Diesel Engine: ISO3046, DIN6271







# QSAND Sanq Power

# Engine Data

Manufacturer/Model	CCEC Cummins KT38-G
No.of Cylinders	12
Displacement	37.8L
Bore and Stroke	159*159(mm)
Compression ratio	15.5:1
Rated RPM	1500rpm
<ul> <li>Max.standby power at rated 1500RPM</li> </ul>	615KW
Aspiration	Turbocharged and Aftercooled
Governor Type	Electronic
<ul> <li>Exhaust Gas Flow @Standby Rating</li> </ul>	2124L/S
<ul> <li>Exhaust Temperature @Standby Rating</li> </ul>	<b>560</b> ℃
<ul> <li>Intake Air Flow@Standby Rating</li> </ul>	755liter/s
Fuel System	Direct Injection Cummins PT
<ul> <li>100%(Prime Power) Load</li> </ul>	140Liter/H
<ul> <li>Lubrication System Min. capacity</li> </ul>	87L
Total Coolant Capacity	111L

### Alternator Data

Manufacture/Type	Stamford/HCI544F	
<ul> <li>Number of phase power</li> </ul>	3	
• Factor	0.8	
Pole Number	4	
Bearing Number	1	
Exciter Type	Brushless, self-excited	
Insulation Class	H/H	
Protection	IP23	

# **Control Panel**



• Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 7320 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.

• Features: receive remote output signal from ATS and realize auto start and stop of generators.

• Auto Mains Failure controller, can realize further more can detect ATS and control directly.

•RS232 or 485 interface which can communicate with PC to realize remote operation.









• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

# Optional

Others

Engine	Alternator	Fuel System	Control System
Pre-heater	<ul> <li>Anti Condensation Heater</li> <li>Drop CT (For Paralleling)</li> </ul>	5	<ul> <li>Remote Control Panel</li> <li>Auto Transfer Switch (ATS)</li> <li>Paralleling System</li> </ul>

Electricity Output Cabinet

# <image>

### Warranty





# QSAND Sanq Power

• Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Cummins gensets enjoy world-wide united Warranty from Cummins engine agency or service centre at the client's local side.

• Service and parts are available from Guangzhou Sanq Power Equipment Co.,Ltd or our distributors in your location.







Data Sheet