SANO Sanq Power



Model: SQC165-6 (S)		
Standby Power (60Hz)	165KVA/132KW	
Prime Power(60Hz)	150KVA/120KW	

Standard Features

• Engine: Cummins 6BTAA5.9-G2

Charge Alternator: 24V

Governer: Electronic

Generator: Stamford UCI274E

Single Bearing Alternator IP23

· Insulation Class H/H

Genuine radiator with engine driven fan

Skid and vibration isolators

· Dry type air filter

Main line circuit breaker (Below 500KVA)

12V battery and cable

User's manual



Weight And Dimensions			
Genset	Dimensions(LxWxH)	Weight (KG)	
Open type	2360mmx830mmx1334mm	1370	
Silent type	3300mmx1150mmx1800mm	2178	

Genera	ator Ra	atings			
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	60	3	0.8	165/132	150/120

Criterion

• Generator sets: GB/T2820-1997, ISO9001: 2008

Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359

· Diesel Engine: ISO3046, DIN6271





SANO Sanq Power

Engine Data	
Manufacturer/Model	DCEC Cummins 6BTAA5.9-G2
No.of Cylinders	6
Displacement	5.9L
 Bore and Stroke 	102*120(mm)
Compression ratio	17.3:1
Rated RPM	1800rpm
 Max.standby power at rated 1800RPM 	145KW
Aspiration	Turbocharged and Charge Air Cooled
Governor Type	Electronic
 Exhaust Gas Flow @Standby Rating 	401L/S
 Exhaust Temperature @Standby Rating 	570 ℃
 Intake Air Flow@Standby Rating 	142liter/s
Fuel System	BYC PB Direct Injection
• 100%(Prime Power) Load	34Liter/H
 Lubrication System Min. capacity 	12.3L
 Total Coolant Capacity 	10L

Alternator Data		
 Manufacture/Type 	Stamford/UCI274E	
 Number of phase power 	3	
• Factor	0.8	
Pole Number	4	
 Bearing Number 	1	
Exciter Type	Brushless, self-excited	
 Insulation Class 	H/H	
Protection	IP23	

Control Panel



- Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 6020 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.
- Features: receive remote output signal from ATS and realize auto start and stop of generators.
- Auto Mains Failure controller, can realize further more can detect ATS and control directly.





SANO Sanq Power



• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

Optional

Engine	Alternator	Fuel System	Control System
Pre-heater	Anti Condensation HeaterDrop CT (For Paralleling	3	Remote Control PanelAuto Transfer Switch (ATS)Paralleling System
			 Electricity Output Cabinet

Others

- Rainproof Type
- Soundproof Type
- Trailer Type
- Container Type
- Spare Parts





















Data Sheet

Warranty

- Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Cummins gensets enjoy world-wide united Warranty from Cummins engine agency or service centre at the client's local side.
- Service and parts are available from Guangzhou Sanq Power Equipment Co., Ltd or our distributors in your location.







