Model: SQC165 (S
------------------

Standby Power (50Hz)	165KVA/132KW
Prime Power(50Hz)	150KVA/120KW

#### **Standard Features**

- Engine: Cummins 6BTAA5.9-G12
- Charge Alternator: 24V
- Governer: Electronic
- Generator: Stamford UCI274F
- Single Bearing Alternator IP23
- Insulation Class H/H
- Genuine radiator with engine driven fan
- Skid and vibration isolators
- Dry type air filter
- Main line circuit breaker (Below 500KVA)
- 12V battery and cable
- User's manual

#### Weight And Dimensions

Genset	Dimensions(LxWxH)	Weight (KG)
Open type	2360mmx830mmx1334mm	1420
Silent type	3200mmx1150mmx1770mm	2110

Generator Ratings					
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	50	3	0.8	165/132	150/120

#### Criterion

- Generator sets: GB/T2820-1997, ISO9001: 2008
- Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359
- Diesel Engine: ISO3046, DIN6271







#### **Engine** Data

5	
Manufacturer/Model	DCEC Cummins 6BTAA5.9-G12
No.of Cylinders	6
Displacement	5.9L
Bore and Stroke	102*120(mm)
Compression ratio	17.3:1
Rated RPM	1500rpm
<ul> <li>Max.standby power at rated 1500RPM</li> </ul>	155KW
Aspiration	Turbocharged & Charge Air Cooled
Governor Type	Electronic
<ul> <li>Exhaust Gas Flow @Standby Rating</li> </ul>	357L/S
<ul> <li>Exhaust Temperature @Standby Rating</li> </ul>	<b>507</b> ℃
<ul> <li>Intake Air Flow@Standby Rating</li> </ul>	150liter/s
Fuel System	BYC P7100/Electronic Governor
<ul> <li>100%(Prime Power) Load</li> </ul>	34Liter/H
<ul> <li>Lubrication System Min.</li> </ul>	16.4L
Total Coolant Capacity	10L

#### Alternator Data

Manufacture/Type	Stamford/UCI274F	
<ul> <li>Number of phase power</li> </ul>	3	
• Factor	0.8	
Pole Number	4	
Bearing Number	1	
Exciter Type	Brushless, self-excited	
Insulation Class	H/H	
Protection	IP23	

#### **Control Panel**



• Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 6020 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.

• Features: receive remote output signal from ATS and realize auto start and stop of generators.

• Auto Mains Failure controller, can realize further more can detect ATS and control directly.









• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

#### Optional

Engine	Alternator	Fuel System	Control System
Pre-heater	<ul> <li>Anti Condensation Heater</li> <li>Drop CT (For Paralleling)</li> </ul>	3	<ul> <li>Remote Control Panel</li> <li>Auto Transfer Switch (ATS)</li> </ul>

- Paralleling System
- Electricity Output Cabinet

#### Others

- Rainproof Type
- Soundproof Type
- Trailer Type
- Container Type
- Spare Parts









### Warranty

• Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Cummins gensets enjoy world-wide united Warranty from Cummins engine agency or service centre at the client's local side.

• Service and parts are available from Guangzhou Sanq Power Equipment Co., Ltd or our distributors in your location.





