### Model: SQD165 (S)

Standby Power (50Hz)	165KVA/132KW
Prime Power(50Hz)	150KVA/120KW

#### **Standard Features**

- Engine: Doosan DP086TA
- Charge Alternator: 24V
- Governer: Electronic
- Generator: Stamford UCI274F
- Single Bearing Alternator IP23
- Insulation Class H/H
- Genuine radiator with engine driven fan
- Skid and vibration isolators
- Dry type air filter
- Main line circuit breaker (Below 500KVA)
- 12V battery and cable
- User's manual

#### Weight And Dimensions

Genset	Dimensions(LxWxH)	Weight (KG)	
Open type	2600mmx870mmx1100mm	2000	
Silent type	3200mmx1133mmx1766mm	2900	

Generator Ratings					
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	50	3	0.8	165/132	150/120

### Criterion

- Generator sets: GB/T2820-1997, ISO9001: 2008
- Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359
- Diesel Engine: ISO3046, DIN6271







#### Engine Data

0	
Manufacturer/Model	Doosan DP086TA
No.of Cylinders	6
Displacement	8.071L
Bore and Stroke	111*139(mm)
Compression ratio	16.7:1
Rated RPM	1500rpm
<ul> <li>Max.standby power at rated 1500RPM</li> </ul>	219KW
Rotation	Counter clockwise viewed from Flywheel
Governor	Electric type ( all speed control )
<ul> <li>Exhaust Gas Flow @Standby Rating</li> </ul>	33.9m3/min
<ul> <li>Exhaust Temperature @Standby Rating</li> </ul>	610℃
<ul> <li>Intake Air Flow@Standby Rating</li> </ul>	14.33m3/min
Fuel System	Mechanical type in injection pump
100%(Prime Power) Load	33.7Liter/H
Coolant flow rate	166 liters / min
Coolant capacity	Engine Only : Approx. 14 lit., With Radiator : Approx 44 lit.(standard)

Alternator Data		
Manufacture/Type	Stamford/UCI274F	
<ul> <li>Number of phase power</li> </ul>	3	
Factor	0.8	
Pole Number	4	
<ul> <li>Bearing Number</li> </ul>	1	
Exciter Type	Brushless, self-excited	
Insulation Class	H/H	
Protection	IP23	

# **Control Panel**

	DSE Deep	Sea Dechooses		7	٦
	0	CONTROL	DSE	ø	
(實		-	JL.		
e.					
6					

- Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 6020 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.
- Features: receive remote output signal from ATS and realize auto start and stop of generators.
- Auto Mains Failure controller, can realize further more can detect ATS and control directly.









• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

### Optional

Engine	Alternator	Fuel System	Control System
Pre-heater	<ul> <li>Anti Condensation Heater</li> <li>Drop CT (For Paralleling)</li> </ul>	3	<ul> <li>Remote Control Panel</li> <li>Auto Transfer Switch (ATS)</li> </ul>

- Paralleling System
- Electricity Output Cabinet

#### Others

- Rainproof Type
- Soundproof Type
- Trailer Type
- Container Type
- Spare Parts









## Warranty

• Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Doosan gensets enjoy world-wide united Warranty from Doosan engine agency or service centre at the client's local side.

• Service and parts are available from Guangzhou Sanq Power Equipment Co.,Ltd or our distributors in your location.





