



Model: SQD19 (S)	
Standby Power (50Hz)	19KVA/15KW
Prime Power(50Hz)	17.5KVA/14KW

#### Standard Features

Engine: Doosan SP224NA

Charge Alternator: 24V

Governer: Mechnical

Generator: Stamford PI044HSingle Bearing Alternator IP23

· Insulation Class H/H

• Genuine radiator with engine driven fan

· Skid and vibration isolators

Dry type air filter

Main line circuit breaker (Below 500KVA)

12V battery and cable

User's manual

Weight And Dimensions			
Genset	Dimensions(LxWxH)	Weight (KG)	
Open type	1260mmx700mmx970mm	380	
Silent type	2200mmx1033mmx1304mm	1070	

Generator Ratings					
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	50	3	0.8	19/15	17.5/14

### Criterion

• Generator sets: GB/T2820-1997, ISO9001: 2008

Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359

· Diesel Engine: ISO3046, DIN6271





# SANO Sanq Power

Engine Data	
Manufacturer/Model	Doosan SP224NA
No.of Cylinders	3
Displacement	2.197 liters
Bore and Stroke	Ø87 x 92.4 mm
Compression ratio	21.7:1
Rated RPM	1500rpm
Rotation	Counter clockwise viewed from Flywheel
Injection timing	14° BTDC
Governor	Mechnical centrifugal + Woodward APECS 4500
Cooling method	Fresh water forced circulation
<ul> <li>Intake Air Flow</li> </ul>	1.33 m³/min
<ul> <li>Exh. gas temp. after turbo.</li> </ul>	480°C
<ul> <li>Exhaust Gas Flow</li> </ul>	1.40m³/min
<ul> <li>Feed pump</li> </ul>	Diaphragm type pump
<ul> <li>Fuel feed pump capacity</li> </ul>	24 liters / hr
<ul> <li>Coolant capacity (Engine Only)</li> </ul>	3.7 liters

Alternator Data		
<ul> <li>Manufacture/Type</li> </ul>	Stamford/PI044H	
<ul> <li>Number of phase power</li> </ul>	3	
<ul> <li>Factor</li> </ul>	0.8	
Pole Number	4	
Bearing Number	1	
• Exciter Type	Brushless, self-excited	
Insulation Class	H/H	
Protection	IP23	

#### Control Panel



- Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 6020 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.
- Features: receive remote output signal from ATS and realize auto start and stop of generators.
- Auto Mains Failure controller, can realize further more can detect ATS and control directly.





### SANO Sanq Power



• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

#### Optional

Engine	Alternator	Fuel System	Control System
Pre-heater	<ul><li>Anti Condensation Heater</li><li>Drop CT (For Paralleling</li></ul>	3	<ul><li>Remote Control Panel</li><li>Auto Transfer Switch (ATS)</li><li>Paralleling System</li></ul>
			<ul> <li>Electricity Output Cabinet</li> </ul>

#### Others

- Rainproof Type
- Soundproof Type
- Trailer Type
- Container Type
- Spare Parts



















## **SANO** Sanq Power



### Warranty

- Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Doosan gensets enjoy world-wide united Warranty from Doosan engine agency or service centre at the client's local side.
- Service and parts are available from Guangzhou Sanq Power Equipment Co., Ltd or our distributors in your location.



