Model :	: SQ[0350	(S)
---------	-------	------	--------------

Standby Power (50Hz)	350KVA/280KW	
Prime Power(50Hz)	318KVA/255KW	

Standard Features

- Engine: Doosan DP126LB
- Charge Alternator: 24V
- Governer: Electronic
- Generator: Stamford HCI444ES
- Single Bearing Alternator IP23
- Insulation Class H/H
- Genuine radiator with engine driven fan
- Skid and vibration isolators
- Dry type air filter
- Main line circuit breaker (Below 500KVA)
- 12V battery and cable
- User's manual

Weight And Dimensions

Genset	Dimensions(LxWxH)	Weight (KG)
Open type	2800mmx900mmx1600mm	2700
Silent type	4300mmx1483mmx2145mm	4490

Generator Ratings					
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	50	3	0.8	350/280	318/255

Criterion

- Generator sets: GB/T2820-1997, ISO9001: 2008
- Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359
- Diesel Engine: ISO3046, DIN6271







Engine Data

Manufacturer/Model	Doosan DP126LB
No.of Cylinders	6
Displacement	11.051 liters
Bore and Stroke	123 x 155 mm
Compression ratio	17.2 : 1
Rated RPM	1500rpm
Max.standby power at rated 1500RPM	346KW
Rotation	Counter clockwise viewed from Flywheel
Governor	Electric type (all speed control)
Exhaust Gas Flow @Standby Rating	58.3m3/min
 Exhaust Temperature @Standby Rating 	590°C
 Intake Air Flow@Standby Rating 	20.9m3/min
Oil capacity	Max. 44 liters , Min. 20 liters
100%(Prime Power) Load	76iters/hr
Fuel feed pump Capacity	315 liters / hr
Coolant Capacity	Engine Only : Approx. 23 lit., With Radiator : Approx.51 lit.(standard)

Alternator Data

Manufacture/Type	Stamford/HCI444ES	
 Number of phase power 	3	
Factor	0.8	
Pole Number	4	
Bearing Number	1	
Exciter Type	Brushless, self-excited	
Insulation Class	H/H	
Protection	IP23	

Control Panel



• Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 6020 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.

• Features: receive remote output signal from ATS and realize auto start and stop of generators.

• Auto Mains Failure controller, can realize further more can detect ATS and control directly.









• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

Optional

Engine	Alternator	Fuel System	Control System
Pre-heater	 Anti Condensation Heater Drop CT (For Paralleling) 	3	 Remote Control Panel Auto Transfer Switch (ATS)

- Paralleling System
- Electricity Output Cabinet

Others

- Rainproof Type
- Soundproof Type
- Trailer Type
- Container Type
- Spare Parts









Warranty

• Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Doosan gensets enjoy world-wide united Warranty from Doosan engine agency or service centre at the client's local side.

• Service and parts are available from Guangzhou Sanq Power Equipment Co.,Ltd or our distributors in your location.





